



Speed Ex™

Cord-electric, Self-Contained Carpet Extractor specifications



Brush Drive System

Brush bristle length	0.9 in / 22 mm
Brush bristle type	Nylon construction, Reverse chevron
Brush diameter	3.5 in / 89 mm
Brush length	15 in / 380 mm
Brush motor power	0.4 hp / 0.3 kW
Brush motor voltage	120 V / 230 V
Brush RPM	1,200 rpm
Motor RPM	2,400 rpm

Chassis / Body Construction

Chassis construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Wheel descriptions	8 in / 200mm

Vacuum System

Airflow at orifice	99 cfm / 2.8 m ³ /min
Vacuum motor amps	7.1 amps/ 3.6 amps
Vacuum motor power	1.2 hp / .89 kW
Vacuum motor stages	2 stage
Sealed waterlift	86 in / 2,180mm

Dimensions (Handle folded flat for storage)

Length	27 in / 690 mm
Machine Width	19 in / 480 mm
Height	28 in / 710 mm
Net weight	102 lb / 46 kg

Solution & Recovery System

Solution tank capacity	5 gal / 19 L
Recovery tank wet capacity	5 gal / 19 L
Spray jet count	2-quick connect

Power Consumption

Amps	10.8 amps / 5.4 amps
Voltage	120 V / 230 V
Watts	1300 watts
Cord	50 ft / 15 m
Electrical Safety Approvals	ETL Tested for UL & CSA Standards

Pump System

Solution pump pressure	65 psi / 4.48 bar
Solution pump amps	.7 amp / .35 amp
Solution pump flow rate	.7 gpm / 2.6 L/min

Sound Level *

Decibel ration @ operators ear	69 dBA
--------------------------------	--------

Warranty

3 years/2500 hrs on parts and labor.
10 years on rotationally-molded polyethylene tanks. No travel.
Please contact your Nobles representative for additional warranty details.

* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA